

IN THE CLAIMS:

Please cancel claim 14 and amend claims 1, 15, and 17 as follows:

1. (Currently Amended) A hand-held massager, comprising:

a housing having a gripping portion and a body-contacting portion, said housing enclosing a pump and a massage liquid reservoir located within said housing, said pump being in fluid communication with said reservoir and being provided with manual volume control of the dispensed massaging liquid;

said body-contacting portion including a heated applicator pad which is generally planar and fixed to said body-contacting portion, said body-contacting portion being configured for emitting heat directly to a target body surface and said housing being configured so that the massaging liquid is emitted by said pump from said body-contacting portion under said manual volume control so that heat is applied by said body-contacting portion to the target body surface and to the emitted liquid; and

a vibration generator disposed in said housing in operational proximity to said body-contacting portion for generating vibrations emitted by said body-contacting portion; and

a pivoting reservoir mount located within said housing, said mount constructed and arranged for receiving said reservoir configured for retaining a supply of the massaging liquid and being pivotable between an operating position and a refill position.

2. (Canceled)

3. (Previously Amended) The massager of claim 1 further including at least one fluid outlet disposed in close proximity to said pad for emitting the massaging liquid.

4. (Original) The massager of claim 3 wherein said heated applicator pad has an outer peripheral edge, and said at least one fluid outlet is disposed in close proximity to said edge.

5. (Original) The massager of claim 1 further including a variable control electrically connected to a heat emitter located on said body-contacting portion for controlling the amount of emitted heat.

6. (Canceled)

7. (Previously Amended) The massager of claim 1 further including a variable control electrically connected to said vibration generator for controlling the amount of emitted vibrations.

8. (Original) The massager of claim 7 wherein said vibration generator is configured to operate in the approximate range of between 1500 to 4000 rpm.

9. (Previously Amended) The massager of claim 1 further including a power source of two 2,000 mah batteries, and wherein said vibration generator and said heat emitting portion of said housing are configured for operating for approximately 40 minutes.

10. (Previously Amended) The massager of claim 1 further including a vibration isolating gasket disposed between said gripping portion and said body-contacting portion.

11. (Original) The massager of claim 1 further including a pocket on said body-contacting portion of said housing and at least one massaging enhancement pad, said pocket configured for receiving said at least one massaging enhancement pad.

12. (Original) The massager of claim 11 wherein said at least one massaging enhancement pad has a surface taken from the group including massaging nodules, waves, fingers, smooth surface and textured pads.

13. (Original) The massager of claim 12 wherein said at least one massaging enhancement pad is removably attached to said pocket.

14. (Canceled)

15. (Currently Amended) The massager of claim 14~~1~~ wherein said housing further includes a removable reservoir cover, and said massager is configured so that, upon removal of said cover from said housing and the placement of said massager to extend in a generally vertically-oriented position, said reservoir mount pivots said reservoir ~~is~~ in a generally parallel position relative to said body-contacting portion so that said reservoir assumes a generally vertical position for refilling.

16. (Canceled)

17. (Currently Amended) A hand-held massager, comprising:
a housing having a gripping portion and a body-contacting portion, said
housing enclosing a pump and a massage liquid reservoir located within said housing,
said pump being in fluid communication with said reservoir and being provided with
manual volume control of the dispensed massaging liquid;

said body-contacting portion including a heated applicator pad which is
generally planar and fixed to said body-contacting portion, said body-contacting portion
being configured for emitting heat directly to a target body surface and said housing
being configured so that the massaging liquid is emitted by said pump from said body-
contacting portion under said manual volume control so that heat is applied by said body-
contacting portion to the target body surface and to the emitted liquid; and

a vibration generator disposed in said housing in operational proximity to said body-contacting portion for generating vibrations emitted by said body-contacting portion; and

~~The massager of claim 1 further including a thumbwheel associated with said housing for controlling said pump, said pump is being~~ disposed within a chamber defined by said thumbwheel.

18. (Previously Amended) A hand-held massager, comprising:

a housing having a gripping portion and a body-contacting portion, said housing being configured for emitting a massaging liquid and said body-contacting portion being configured for emitting heat to a target skin surface;

a pump disposed within said housing for dispensing the massaging liquid;

a removable reservoir being in fluid communication with said pump; and

said reservoir being pivotably mounted to said massager between an operational position in which said reservoir is inclined relative to said body-contacting portion, and a refill position in which said body-contacting portion is placed in a generally vertical position and said reservoir is in a generally parallel position relative to a body contacting surface of said body-contacting portion.

19. (Original) The massager of claim 18 wherein said gripping portion includes a removable reservoir cover configured for providing access to said reservoir.

20. (Canceled)

21. (Canceled)

22. (Withdrawn)

23. (Withdrawn)